

A4 316 Equivalent Corrosion Resistance

0-1km

Hilti Corrosion handbook / DFTM

$\leq 0,5 \text{ mm} / 0,02''$
 $\geq 8 \text{ mm} / 0,32''$
 $\leq 0,5 \text{ mm} / 0,02''$

Use with					
X-BT-MR M6/10 SN 8	TX-BT 4.7/7 80	DX 351-BT	X-BT 1/4" - 20Nm/ 14,8 ft lb	X-NSD 1/4" - 10 mm	X-BT Drilling Jig

$\geq 8 \text{ mm}$

1

SF BT 22-A
SF BT 18-A

2a

2b

The drill bit may experience a significant reduction in lifetime when used on high strength steels. Consult Hilti for more info.

3a

3b

4

DX 351 BT

100x

4a

5

X-BT-MR M6

6

$\leq 200 \text{ N}$

7

9

$\leq 6,5 - 6,7 \text{ mm}$
 $1-10 \text{ mm} / 5/64'' - 25/64''$

8a

Max. X-BT: 26.8 mm

Max. X-BT: 26.8 mm

8b

Min. X-BT: 25.7 mm

Min. X-BT: 25.7 mm

10a

X-BT 1/4" 20Nm / 14.8 lb-ft

2

1

3 click!

STOP

10b

SF 14-A	3	12
SF 10W	4	8
SF 8M-A22	4	12
SFC 14-A	2	13
SFC 22-A	2	14
SF 6-A22	1	1

$\leq 5 \text{ N}$

10c

$\leq 20 \text{ Nm} / 14.8 \text{ lb-ft}$

T_{inst}

A4 316 Equivalent Corrosion Resistance

0-1km

Hilti Corrosion handbook / DFTM

$\leq 0,5 \text{ mm} / 0.02''$
 $\geq 8 \text{ mm} / 0.32''$
 $\leq 0,5 \text{ mm} / 0.02''$

Use with					
X-BT-MR M6/10 SN 8	✓	TX-BT 4.7/7 80			

$\geq 8 \text{ mm}$

1

SF BT 22-A
SF BT 18-A

2a

2b

The drill bit may experience a significant reduction in lifetime when used on high strength steels. Consult Hilti for more info.

3

BX 3-BT

5b

6

X-BT-MR M6

10

$\text{Ø } 6,5 - 6,7 \text{ mm}$
 $1 - 10 \text{ mm}$
 $5/64'' - 25/64''$

3a

3b

7

$\leq 150 \text{ N}$

8

11a

X-BT 1/4" 20Nm / 14.8 lb-ft

2

1

3 click!

4

X-FG B3-BTG

X-FG B3-BT M/W

EJECT

9a

Max.

X-BT: 26.8 mm

9b

Min.

X-BT: 25.7 mm

Max.

X-BT: 26.8 mm

Min.

X-BT: 25.7 mm

11b

SF 14-A	3	12
SF 10W	4	8
SF 8M-A22	4	12
SFC 14-A	2	13
SFC 22-A	2	14
SF 6-A22	1	1

$\leq 5 \text{ N}$

11c

$\leq 20 \text{ Nm}$
14.8 lb-ft

T_{inst}